

SATSTREAM 21401

MPEG / DATA SATELLITE UPLINK MODULATOR



FEATURES

- Moderate speed data and/or MPEG CD Quality Audio
- Versions are available for SCPC and FM Subcarrier
- Software configuration via serial port or downlink
- Flexible bandwidth allocation between audio and data
- QPSK modulation with Viterbi error correction
- Alarm output signals for modulator output faults
- Selective addressing to units, groups, regions or all

DESCRIPTION

The 21401 Modulator features state of the art design for flexibility and reliability. While designed primarily for distribution of broadcast quality audio, it may also serve as a moderate speed data uplink modulator. The user has complete flexibility in allocation of the available bandwidth.

The data channel may be used for global distribution or data packets may be directed to specific receivers selected by group code, region code, or by individual serial number. Each receiver may be enabled to receive 1 or more of up to 8192 streams (such as news wires).

Among many options is status and trouble reporting via a serial data port or a telephone modem using a simple ASCII protocol. In some applications the output failure contact closure output may be used to automatically switch over to a backup modulator or transmitter rack.

The SatStream 21401 is available in a standard L band SCPC version as well as an optional FM subcarrier version. The 1 RU Rack Mount version is standard, a smaller footprint desktop version is also available. The modulator includes a switchmode universal AC power supply.

APPLICATIONS

- High quality audio distribution for networks
- Automated broadcast station control and cueing
- Low to moderate speed data for news feeds
- Corporate data distribution networks
- Selective distribution of news to enable clients
- Background music systems with local insertion
- Downlink of internet feed to remote locations

EMERGENCY ALERT- OPTION Z

SCPC QPSK is a simple and time proven technology that does not need to rely on complex terrestrial infrastructure making it ideal for mission critical communications that must work faultlessly in time of disaster. The EAS option provides additional features that allow the receiver to act as a repeater for EAS notifications. All segments of the standard EAS broadcast are digitized and packetized at the uplink modulator for transmission as control packets.

Approximately 10000 bits per second of the data stream are dedicated to the EAS broadcast when it is enabled. At the receiver the incoming EAS packets are interpreted. Precision frequency Alert Tones and FSK data are locally synthesized in the receiver. EAS audio is inserted in the audio output stream in accordance with the timing captured at the uplink modulator. By regenerating all tones and voice messages locally, distortion and possible corruption of the data is minimized. A push to talk signal may be sent to activate dispatch systems automatically. A loss-of-signal alert output is also provided. When not carrying an active EAS message, the available bandwidth may be used to transmit other data, text or graphics.

SatStream Systems Corporation 2- 2599 Cedar Park Place Abbotsford, BC V2T 3S4 Canada
TEL 604 859 5528 FAX 604 859 5529 e-mail sales@satstream.ca

U.S. Mailing Address: SatStream PO Box 1297 Sumas, WA 98295 USA

SATSTREAM 21401 SPECIFICATIONS

Output Frequency Range	SCPC Version (Option A) 50.00 – 90.00 MHz SCPC Version (Option B) 950 – 1450 MHz (standard L band) SCPC Version (Option B1) 950 – 1750 MHz (extended L band) Subcarrier Version (Option F) 100 KHz – 8.995 MHz
Frequency resolution	SCPC 1 KHz or better Subcarrier 100 Hz
Frequency accuracy	Within +/- 1 ppm (12 KHz at Ku band)
Uplink output reference	10.000 MHz within +/- 1 part per million Aging of less than 1 ppm per year
Modulation	QPSK with spectral shaping to minimize bandwidth Pseudorandom scrambling for energy dispersal
Forward Error Correction	Viterbi 1/2 3/4 K=7
MPEG Data Rates (Option M)	Standard rates from 32000 to 320000 bits/second
Maximum total data rate	375000 bits/second including MPEG, Data, Aux Audio
Audio Input (Option M)	Two channels balanced 600 ohm, digital level adjust Accepts 20 Hz – 20 KHz at higher data rates
Audio Dynamic Range (Option M)	Greater than 85 db
Aux Audio Input (Option V or Z)	Single channel voice grade audio, unbalanced input
Control/Supervisory Serial Port	DB9 RS232 Configurable rates 2400-57600 bps
Auxiliary Serial Data Port	DB9 RS232 or RS485 Configurable rates 2400-250000 bps
Relay Contact Closure Port	1 General Fault NO contact (Form A) 1 No modulation input for XX seconds NO contact (Form A)
Power requirements	90-260 VAC 48-63 Hz less than 30 VA
Dimensions	Standard rack mount: 1RU 19" Rack 19" wide x 1.75" high by 7.0" deep (48.26 x 4.45 x 17.8 cm) Option T: Desktop Version 10.5" wide x 1.85" high x 7.0" deep (26.7 x 4.7 x 17.8 cm)

DESCRIPTION OF OPTIONS FOR MODEL 21401	
A:	SCPC output Frequency 50.00 – 90.00 MHz
B:	SCPC output Frequency 950 – 1450 MHz
B1:	SCPC output Frequency 950 – 1750 MHz
C:	FM Subcarrier output freq 100 KHz – 8.995 MHz
E:	Ethernet LAN interface Supervisory and control port
M:	MPEG Audio Input Monaural or stereo analog output
N:	Selective Addressing Data channel selective addressing
P:	Telephone modem Supervisory and control port including SMTP
R:	Remote programming Remote or downlink programming control
S:	LCD Status Display Display and keypad for local manual setup
T:	Desktop package Desktop instead of normal rack mount configuration
V:	Voice grade audio An additional compressed voice grade channel

